

t2

Refined hydration. Digital precision.



Overview

- Next-generation integrated tap
- Refined hydration
- Ultra-compact, durable ProCore®
- Digital precision
- Energy-efficient
- Easy-to-fit ventilation kit
- Advanced UV protection built-in
- Totality® is our unique methodology designed to ensure our appliances provide an exceptional standard of hygiene.

Specifications

- Chilled temperature - 2°C
- ProCore+ chilled & sparkling capacity - 80L/h
- ProCore chilled & sparkling capacity - 50L/h
- Dispense height - 310
- Tap height - 390

Accessories

- [500ml water bottles](#)
- [Printed paper cups 463428](#)
- [Install kit with 3M filter 461202](#)
- [Refill station cabinet 601604](#)

T2 ProCore W320xD375xH335mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	742000	742010	742020	742030
Chilled & Sparkling	Dry Chill®	200W	742080	742090	742100	742110
Chilled, Ambient & Sparkling	Dry Chill®	200W	742160	742170	742180	742190

T2 ProCore+ W320xD375xH350mm

Dispense Options	Water system	Max power consumption	Black	Steel	Black LED-UV	Steel LED-UV
Chilled & Ambient	Dry Chill®	140W	742240	742250	742260	742270
Chilled & Sparkling	Dry Chill®	200W	742320	742330	742340	742350
Chilled, Ambient & Sparkling	Dry Chill®	200W	742400	742410	742420	742430

Simple-fit Ventilation Base
W322xD431xH60mm
(Includes 20mm overhang)

borg & overström

Find out more:

<https://www.borgandoverstrom.com/en/p/tap-systems/t2/>